

# TERRA *Tyre*

## MULTI S

### DURABILITY AND STABILITY FOR E3/L3 APPLICATION

- ➔ Non-directional traction and standard tread depth pattern design
- ➔ Excellent compound performance supported with low heat build up
- ➔ Primarily designed for mining, off road and muddy surfaces



SIZE	STAR RATING	TYPE	TRA CODE	STANDARD RIM	TREAD DEPTH (MM)	LOAD INDEX	SECTION WIDTH (MM)	OVERALL DIAMETER	MAX LOAD & INFLATION PRESSURE (kg/kpa)	
						TRA			50 KM/H	10KM/H
17.5R25	★★	TL	E3/L3	14.00/1.5	26.5	167B/182A2	445	1348	5450/525	8500/650
20.5R25	★★	TL	E3/L3	17.00/2.0	28.5	177B/193A2	520	1492	7300/525	15000/650
23.5R25	★★	TL	E3/L3	19.5/2.5	32	185B/201A2	597	1617	9250/525	14500/650
26.5R25	★★	TL	E-3/L-3	22.00/3.0	35	209A2/193B	673	1750	11500/525	18500/650
29.5R25	★★	TL	E-3/L-3	25.00/3.5	43	200B/216A2	750	1873	14000/525	22400/650



TYRES • WHEELS • SERVICE

[OTRTyres.com](http://OTRTyres.com)